

NPD2-2000-8000

2-Way, 2~8GHz

Features:

- * Small Size
- * Low Insertion Loss

Applications:

- * Amplifiers
- * Mixers
- * Antennas
- * Laboratory Test

Electrical

Frequency:	2~8GHz
Insertion Loss:	0.6dB max. (SMA) 0.8dB max. (N)
Input VSWR:	1.3 max.
Output VSWR:	1.2 max.
Isolation:	20dB min. (SMA) 18dB min. (N)
Amplitude Balance:	0.2dB max. (SMA) ±0.2dB (N)
Phase Balance:	±3°
Impedance:	50Ω
Average Power:	30W max. 2W max. as combiner


Mechanical

Mounting:	3-Φ2.7mm through-hole (SMA) 3-Φ3.2mm through-hole (N)
-----------	--

Environmental

Operation Temperature:	-45~+85°C
------------------------	-----------

Outline Drawings



Unit: mm [in]

Tolerance: ±0.5mm [±0.02in]

How To Order

NPD2-2000-8000-X-Y

X: Average power as divider

Y: Connector type

Connector naming rules:

S - SMA Female (Outline A)

N - N Female (Outline B)

Examples:

To order a 2-way power divider, 2~8GHz, 30W, N female, specify NPD2-2000-8000-30-N.

Customization is available upon request.