

## NCK-K-40-1

### 2.92mm Connectors, DC~40GHz, Precision type

Features:  
\* High Precision

Applications:  
\* Calibration  
\* Laboratory Test



#### Description

With the components in these kits you can make error-corrected measurements of devices supplied with 2.92mm connectors from DC to 40 GHz.

#### Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size			
		(GHz)	(Ω)	(Max.)	(°, Max.)			(mm)			
NOKC-M-40-1	2.92mm male open	DC~40	50	-	±6	Gold plated beryllium copper	Gold plated beryllium copper	-			
NOKC-F-40-1	2.92mm female open								-	±4.5	-
NSKC-M-40-1	2.92mm male short			-	-			-			
NSKC-F-40-1	2.92mm female short								-	-	-
NCT-K-C-M-40-1	2.92mm male termination			-	-			-			
NCT-K-C-F-40-1	2.92mm female termination								-	-	-
NW-K1-CK	2.92mm torque wrench			-	-			Nickel plated tool steel (Head)			
NAKCC-MM*	2.92mm male to 2.92mm male adapter			1.15	-			-	Gold plated beryllium copper	Gold plated beryllium copper	-
NAKCC-MF*	2.92mm male to 2.92mm female										
NAKCC-FF*	2.92mm female to 2.92mm female										
Storage Box		-	-	-	-	Wood	275*200*80/ 145*145*60				

\*"\*" Equal phase adapter

#### How To Order

- NCK-K-40-1-10** All the 10 components in one box.
- NCK-K-40-1-3M** Three in one box, including open, short and termination, male, NOKC-M-40-1, NSKC-M-40-1, NCT-K-C-M-40-1.
- NCK-K-40-1-3F** Three in one box, including open, short and termination, female, NOKC-F-40-1, NSKC-F-40-1, NSKC-F-40-1.
- NCK-K-40-1-6** Six in one box, including NCK-K-40-1-3M and NCK-K-40-1-3F.

To order a single component, specify the part number in the first column.