

NCK-N-18-1

N Connectors, DC~18GHz, Precision type

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with N connectors from DC to 18 GHz.

Components

Part Number	Description	Frequency (GHz)	Impedance (Ω)	VSWR (Max.)	Phase Accuracy (°, Max.)	Inner Conductor	Outer Conductor	Size (mm)			
NONC-M-18-1	N male open	DC~18	50	-	±1	Gold plated beryllium copper	Passivated stainless steel	-			
NONC-F-18-1	N female open			-				-			
NSNC-M-18-1	N male short			-	±1			-			
NSNC-F-18-1	N female short			-				-			
NCT-N-C-M-18-1	N male termination			-	1.048			-	-		
NCT-N-C-F-18-1	N female termination			-				-	-		
NW-N1-CK	N torque wrench			-	-			-	Tool steel (Head)	Aluminium, anodised (Handle)	19.1 (Opening size)
NANNC-MM-1*	N male to N male adapter			-	-			-	Gold plated beryllium copper	Passivated stainless steel	-
NANNC-MF-1*	N male to N female adapter			1.06	-			-			-
NANNC-FF-1*	N female to N female adapter			-	-			-			-
Storage Box		-	-	-	-	Wood		275*200*80/ 145*145*60			

* ** Equal phase adapter

How To Order

- NCK-N-18-1-10** All the 10 components in one box.
- NCK-N-18-1-3M** Three in one box, including open, short and termination, male, NOKC-M-18-1, NSKC-M-18-1, NCT-K-C-M-18-1.
- NCK-N-18-1-3F** Three in one box, including open, short and termination, female, NOKC-F-18-1, NSKC-F-18-1, NCT-K-C-F-18-1.
- NCK-N-18-1-6** Six in one box, including NCK-N-18-1-3M and NCK-N-18-1-3F.

To order a single component, specify the part number in the first column.