

NAPP SMP to SMP

Features:
* Low VSWR

Applications:
* Wireless
* Transmitter
* Laboratory Test
* Radar



Electrical

Frequency: DC~6GHz (only NAPP-FF-4)
DC~18GHz
VSWR: 1.3 max.
1.35 max. (Outline B, E)
Impedance: 50Ω


Environmental

Temperature: -55~+125°C


Mechanical

RF Connectors: SMP
Mating Life Cycle: 500 cycles
Outer Conductor: Passivated Stainless Steel (Outline F)
Gold Plated Brass (Outline A, G, H)
Gold Plated Beryllium Copper (Outline B, C, D, E, F)
Dielectric: PTFE
Inner Conductor: Gold Plated Beryllium Copper


Outline Drawings




Outline A




Outline B




Outline C




Outline D




Outline E



Outline F



Outline G



Outline H

Unit: mm [in]
Tolerance: ±0.2mm [±0.008in]



Coaxial Adapters

How To Order

NAPP-MM - SMP(m) to SMP(m), Outline A

NAPP-MF - SMP(m) to SMP(f), Outline B

NAPP-FF - SMP(f) to SMP(f), 18GHz, Outline C

NAPP-FF-1 - SMP(f) to SMP(f), Outline D

NAPP-FF-2 - SMP(f) to SMP(f), Outline E

NAPP-FF-3 - SMP(f) to SMP(f), Outline F

NAPP-FF-4 - SMP(f) to SMP(f), 6GHz, Outline C

NAPPL-MM - SMP(m) to SMP(m), Flange mount, Outline G

NAPPL-MM-1 - SMP(m) to SMP(m), Flange mount, Outline H

Customization is available upon request

