

NDI2123B

High Power, High Isolation

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:

- * Wireless
- * Radar
- * Laboratory Test


Description

NDI2123B series Drop-In Isolators cover frequency range 4000~8000MHz. High power, high isolation and low insertion loss make it ideal for a lot of applications like amplifiers, transceivers, etc.

Specifications

Frequency (MHz)	Bandwidth (MHz)	Insertion Loss (dB Max.)	Isolation (dB Min.)	VSWR (Max.)	Fwd Power (W Max.)	Rev Power (W)	Temperature (°C)
4000~8000	4000	0.60	18.0	1.35	60	20	0~+60
5600~7000	1400	0.50	18.0	1.30	60	20	0~+60
5800~6800	1000	0.50	19.0	1.30	60	20	0~+60
6000~8000	2000	0.40	18.0	1.30	60	20	0~+60

Outline Drawings



Unit: mm [inch]

Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]

Mechanical

Size^{*1}: 21*22.5*15mm
0.827*0.886*0.591in

Connector Type: Strip line

Mounting: 3-Φ2.5mm through-hole

[1] Exclude connectors and terminations.

How To Order

NDI2123B-X-Y-Z

X: Start frequency in MHz

Y: Stop frequency in MHz

Z: Reverse Power in W

Examples:

To order a NDI2123B series Isolator, 6000~8000MHz, 20W, specify NDI2123B-6000-8000-20.

Customization is available upon request.