

K346 Series

0.01 GHz to 67 GHz



Broadband Calibrated Coaxial Noise Sources for Noise Figure Measurements

KTB K346 Series - Broadband Calibrated Coaxial Noise Sources are designed for precision noise figure measurement applications, offering exceptional accuracy and reliability.

With low VSWR, they significantly reduce multiple reflections, enhancing measurement accuracy and minimizing uncertainty.

Each unit includes calibrated ENR reports traceable to NIST and VSWR on/off data, with flatness better than ± 1.0 dB over the frequency range.

Standard operation requires +28Vdc with a maximum current draw of 30mA, while custom voltage, output levels, and frequencies are also available.

Model	Frequency Range (GHz)	Output ENR (dB)	I (max) (mA)	Connector
K346A	0.01-18	5-7	30	SMA (M)
K346B	0.01-18	14-16	30	SMA (M)
K346C	0.1-26.5	13-17	30	APC3.5 (M)
K346ka	0.1- 40	10-17	30	K Male**
K346V	0.1-67	7-21	30	V(M)

Specifications

Input Voltage via BNC(F):	+28 +/-2 Vdc
Noise Output Temperature Variation:	< 0.009 dB/ deg C
Noise Output Variation:	< 0.002 dB/% Δ V
Maximum Reverse Power:	1 Watt
Operating Temperature:	0°C to +55°C
Storage Temperature:	-65°C to +125°C
Calibration Points:	10 MHz, every GHz

Key Features

- **Broadband Coverage:** Ideal for a wide range of noise figure measurement and built-in test applications.
- **Superior Stability:** Outstanding temperature and voltage stability ensures consistent performance.
- **Precision and Compatibility:** Noise figure meter-compatible with 6, 15, and 23 dB ENRs (Excess Noise Ratios).
- **Industry Standard Design:** Compact housing with various connector options for easy integration.



KTBS SOLUTIONS INC.

1754 Technology DR STE 122
 San Jose, CA, 95110 ,USA
 Tel: +1 650 686 1019
 E-mail: sales@ktbsolutions.com
 Web: www.ktbsolutions.com