

NSI10

High Power, High Isolation

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:

- * Wireless
- * Radar
- * Laboratory Test

Description

NSI10 series Surface Mount Isolators cover frequency range 2515~5300MHz. High power, high isolation and low insertion loss make it ideal for a lot of applications like amplifiers, transceivers, etc.

Specifications

Frequency (MHz)	Bandwidth (MHz)	IL (dB Max.)	Isolation (dB Min.)	VSWR (Max.)	Fwd Power (W Max.)	Rev Power (W)	Temperature (°C)
2515-2675	160	0.40	16.0	1.40	30	5	-40 ~ +85
2600-2800	200	0.60	17.0	1.35	30	5	-40 ~ +85
4800-5100	300	0.40	20.0	1.25	30	5	-40 ~ +85
5100-5300	200	0.40	20.0	1.25	30	10	-40 ~ +85

Mechanical

Size: $\Phi 10 \times 7\text{mm}$
 $\Phi 0.394 \times 0.276\text{in}$

How To Order

NSI10-V-W-X-Y-Z

V: Start frequency in MHz
W: Stop frequency in MHz
X: Forward power in W
Y: Reverse power in W
Z: Direction type

Direction Naming Rules:





- 1 - Clockwise
- 2 - Anticlockwise

Examples:

To order a NSI10 series Isolator, 2515-2675MHz, Forward power 30W, Reverse power 5W, Clockwise, specify NSI10-2515-2675-30-5-1.

Customization is available upon request.

Outline Drawings



Unit: mm [inch]

Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]

NSI12R5

High Power, High Isolation

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:

- * Wireless
- * Radar
- * Laboratory Test

Description

NSI12R5 series Surface Mount Isolators cover frequency range 800-6000MHz. High power, high isolation and low insertion loss make it ideal for a lot of applications like amplifiers, transceivers, etc.

Specifications

Frequency (MHz)	Bandwidth (MHz)	IL (dB Max.)	Isolation (dB Min.)	VSWR (Max.)	Fwd Power (W Max.)	Rev Power (W)	Temperature (°C)
790-810	20	0.4	20	1.25	50	10	-40 - +85
889-909	20	0.4	20	1.25	50	10	-40 - +85
1180-1220	40	0.4	18	1.25	50	10	-40 - +85
1400-1500	100	0.6	18	1.3	50	10	-40 - +85
1420-1450	30	0.4	20	1.25	50	10	-40 - +85
2200-2300	100	0.3	23	1.2	50	10	-40 - +85
3100-3500	400	0.3	17	1.35	50	10	-40 - +85
4400-5000	600	0.4	20	1.25	30	5	-40 - +85
5500-6000	500	0.4	20	1.25	50	10	-40 - +85
5700-5900	200	0.4	20	1.25	50	10	-40 - +85

Mechanical

Size: $\Phi 12.5 \times 7\text{mm}$
 $\Phi 0.492 \times 0.276\text{in}$

How To Order

NSI12R5-V-W-X-Y-Z

V: Start frequency in MHz

W: Stop frequency in MHz

X: Forward power in W

Y: Reverse power in W

Z: Direction type

Direction Naming Rules:


1 - Clockwise

2 - Anticlockwise

Examples:

To order a NSI12R5 series Isolator, 790-810MHz, Forward power 50W, Reverse power 10W, Clockwise, specify NSI12R5-790-810-50-10-1.

Outline Drawings



Unit: mm [inch]

Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]

Customization is available upon request.

NSI25R4

High Power, High Isolation

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:

- * Wireless
- * Radar
- * Laboratory Test

Description

NSI25R4 series Surface Mount Isolators cover frequency range 350-4000MHz. High power, high isolation and low insertion loss make it ideal for a lot of applications like amplifiers, transceivers, etc.

Specifications

Frequency (MHz)	Bandwidth (MHz)	IL (dB Max.)	Isolation (dB Min.)	VSWR (Max.)	Fwd Power (W Max.)	Rev Power (W)	Temperature (°C)
1030	-	0.30	23.0	1.20	300	20	-40 ~ +85

Mechanical

Size: $\Phi 25.4 \times 9.5\text{mm}$
 $\Phi 1 \times 0.374\text{in}$

How To Order

NSI25R4-V-W-X-Y-Z

V: Start frequency in MHz
W: Stop frequency in MHz
X: Forward power in W
Y: Reverse power in W
Z: Direction type

Direction Naming Rules:





- 1 - Clockwise
- 2 - Anticlockwise

Examples:

To order a NSI25R4 series Isolator, 1030MHz, Forward power 300W, Reverse power 20W, Clockwise, specify NSI25R4-1030-K3-20-1.

Customization is available upon request.

Outline Drawings



Unit: mm [inch]

Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]